

□ **Cleaning of semipermeable membranes in filtration units**

L20 ANSWER 9 OF 121 HCA COPYRIGHT 2002 ACS FAMILY 4  
AN 87:156960 HCA  
IN Sano, Takezo; Shimomura, Takatoshi; Sasaki, Masao  
PA Sumitomo Chemical Co., Ltd., Japan  
SO Japan. Kokai, 3 pp.  
CODEN: JKXXAF  
DT Patent  
LA Japanese  
FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 52058078	A2	19770513	JP 1975-134314	19751108
AB	A contaminated semipermeable <b>membrane</b> (parallel flow) filter unit (reverse osmosis or ultrafiltration) is regularly flushed in a short period with a high pressure gas to contact the <b>membrane</b> with a <b>gas-liq. mixt.</b> , thus <b>removing</b> the <b>contaminated</b> layer. The method is used for any shape of unit. Thus, a tubular cellulose acetate [9004-35-7] <b>membrane</b> filter unit for tap water was used 200 h, then flushed 3 min with N at 35 kg/cm <sup>2</sup> . The salt removal was 94.8% initially, 89.7% after 200 h use, and 94.7% after cleaning.				